

Marine Generator Set Specifications

	Model	kW	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in.) Housed/Unhoused						Weight kg (lb)	
GASOLINE	5E	5.0	60	2	3600	1	120	41.7	773	(30.4)	460	(18.1)	458	(18.0)	99	(218)
	4EF	4.0	50		3000		120/240 110 110/220 220	41.7/20.8 36.4 36.4/18.2 18.2	721	(28.4)	386	(15.2)	429	(16.9)	91	(201)
	7.3E	7.3	60	2	3600	1	120	60.8	773	(30.4)	460	(18.1)	458	(18.0)	99	(218)
	6EF	6.0	50		3000		120/240 110 110/220 220	60.8/30.4 54.6 54.6/27.3 27.3	721	(28.4)	386	(15.2)	429	(16.9)	91	(201)
	10EG	10.0	60	4	1800	1	120/240	83.3/41.7	Not available housed						231	(509)
	13EG	13.0	60	4	1800	1	120/240	108.3/54.2	Not available housed						245	(540)
	15EG	15.0	60	4	1800	1	120/240	125/62.5	Not available housed						259	(571)
	15C	15.0	60	4	1800	1	120/240	125/62.5	Not available housed						340	(749)
	12.5CF	12.5	50		1500		110/220	113.6/56.8	1279	(50.4)	572	(22.5)	726	(28.6)		
	20C	20.0	60	4	1800	1	120/240	166.7/83.3	Not available housed						340	(749)
17.5CF	17.5	50		1500		110/220	159.1/79.5	1305	(51.4)	572	(22.5)	726	(28.6)			
DIESEL	4EOZ	3.5	60	1	3600	1	120	29.2	560	(22.0)	390	(15.4)	490	(19.3)	95	(209)
	3.5EFOZ	3.2	50		3000		230	13.9	Not available unhoused							
	5EOZ	5.0	60	3	1800	1	120	41.7	800	(31.5)	543	(21.4)	610	(24.0)	218	(480)
	4EFOZ	4.0	50		1500		120/240 110/220 220 240	41.7/20.8 36.4/18.2 18.2 16.7	733	(28.9)	471	(18.5)	556	(21.9)	188	(414)
	8EOZD	8.0	60	3	1800	1	120	66.7	877	(34.5)	566	(22.3)	616	(24.3)	243	(536)
	6.5EFOZD	6.5	50		1500		120/240 115/230 230 240	66.7/33.3 56.5/28.3 28.3 24.2	774	(30.5)	463	(18.2)	585	(23.0)	208	(458)
	10EOZD	10.0	60	3	1800	1	120	83.3	934	(36.8)	578	(22.8)	664	(26.1)	306	(674)
	9EFOZD	9.0	50		1500		120/240 115/230 230 240	83.3/41.7 78.3/39.1 39.1 37.5	850	(33.5)	520	(20.5)	617	(24.3)	259	(571)
	13EOZD	13.0	60	3	1800	1	120/240	108.4/54.2	1048	(41.3)	635	(25.0)	690	(27.2)	332	(732)
	11EFOZD	11.0	50		1500		115/230 230 240	95.7/47.8 47.8 45.8	923	(36.3)	563	(22.2)	659	(25.9)	297	(655)
	15.5EOZD	15.5	60	3T	1800	1	120/240	129.2/64.6	1048	(41.3)	635	(25.0)	690	(27.2)	338	(745)
	13EFOZD	13.0	50		1500		115/230 230 240	113.0/56.5 56.5 54.2	923	(36.3)	563	(22.2)	659	(25.9)	302	(666)
	20EOZD	19.0	60	4	1800	1	120/240	158.4/79.2	1137	(44.8)	635	(25.0)	690	(27.2)	375	(827)
	17EFOZD	16.0	50		1500		115/230 230 240	139.1/69.6 69.6 66.7	1042	(41.0)	563	(22.2)	659	(25.9)	340	(749)
	23EOZD	22.0	60	4T	1800	1	120/240	184/92	1137	(44.8)	635	(25.0)	690	(27.2)	387	(853)
	20EFOZD	19.0	50		1500		115/230 230 240	165.2/82.6 82.6 77.1	1042	(41.0)	563	(22.2)	659	(25.9)	352	(776)
	28EOZD	28.0	60	4	1800	1	120/240	233.4/116.7	1295	(51.0)	635	(25.0)	810	(31.9)	587	(1294)
	23EFOZD	23.0	50		1500		115/230 230 240	200.0/100.0 100.0 95.8	1178	(46.4)	635	(25.0)	740	(29.1)	542	(1195)
28EOZD	28.0	60	4	1800	1	120/240	116.7	1295	(51.0)	635	(25.0)	810	(31.9)	587	(1294)	
23EFOZD	23.0	50	4	1800	3	120/240	84.3	1178	(46.4)	635	(25.0)	740	(29.1)	542	(1195)	
					1500	1	120/240 139/240 277/480	84.3 42.1								
32EOZD	32.0	60	4	1800	3	120/240	133.3	1295	(51.0)	635	(25.0)	810	(31.9)	587	(1294)	
					1500	1	115/230 230 240	117.4 112.5								
27EFOZD	27.0	50	4	1800	3	120/240	96.3	1178	(46.4)	635	(25.0)	740	(29.1)	542	(1195)	
					1500	1	139/240 277/480 115/230 110/190 115/230 120/208 230/400 240/416	96.3 48.2 117.4 102.7 84.8 93.8 48.8 46.9								

The power to be at home on the water.

KOHLER
POWER SYSTEMS

Model	kW	Hz	Cyl	RPM	Ph	Voltage	Amps	Length x Width x Height mm (in.)						Weight kg (lb)	
								Housed		Unhoused		Housed		Unhoused	
40EOZ	40.0	60	4	1800	1	120/240	129.0	1667	(65.6)	767	(30.2)	1035	(40.7)	905	(1995)
						120/208	132.0	1549	(61.0)	767	(30.2)	956	(37.6)	828	(1825)
33EFOZ	33.0	50		1500	1	120/240	110.0								
						139/240	120.0								
50EOZ	50.0	60	4T	1800	1	120/240	200.0	1787	(70.4)	767	(30.2)	1035	(40.7)	987	(2175)
						120/208	174.0	1657	(65.2)	767	(30.2)	956	(37.6)	900	(1984)
40EFOZ	40.0	50		1500	1	120/240	151.0								
						139/240	151.0								
65EOZ	65.0	60	4T	1800	1	120/240	250.0	1870	(73.6)	767	(30.2)	1035	(40.7)	1100	(2424)
						120/208	226.0	1737	(68.4)	767	(30.2)	956	(37.6)	1036	(2283)
55EFOZ	55.0	50		1500	1	120/240	196.0								
						139/240	196.0								
80EOZ	80.0	60	6T	1800	1	120/240	250.0	2127	(83.7)	811	(31.9)	1035	(40.7)	1212	(2671)
						120/208	273.0	2004	(78.9)	811	(31.9)	956	(37.6)	1168	(2574)
70EFOZ	70.0	50		1500	1	120/240	236.0								
						139/240	241.0								
99EOZ	99.0	60	6T	1800	1	120/240	325.0	2127	(83.7)	811	(31.9)	1035	(40.7)	1225	(2700)
						120/208	344.0	2004	(78.9)	811	(31.9)	956	(37.6)	1181	(2603)
80EFOZ	80.0	50		1500	1	120/240	298.0								
						139/240	298.0								
125EOZ	125.0	60	6T	1800	1	120/240	391.0	2450	(96.5)	811	(31.9)	1128	(44.4)	1715	(3780)
						120/208	434.0	2291	(90.2)	811	(31.9)	1057	(41.6)	1557	(3432)
100EFOZ	100.0	50		1500	1	120/240	376.0								
						139/240	376.0								
150EOZ	150.0	60	6T	1800	1	120/240	416.0	2450	(96.5)	811	(31.9)	1128	(44.4)	1728	(3809)
						120/208	521.0	2291	(90.2)	811	(31.9)	1057	(41.6)	1569	(3458)
125EFOZ	125.0	50		1500	1	120/240	451.0								
						139/240	451.0								

DIESEL

KohlerPowerSystems.com/marine



Printed in U.S.A. G12-271
© 2003 by Kohler Co. 5/04

KOHLER CO.
KOHLER, WISCONSIN 53044

TEL. 920-565-3381
FAX 920-459-1646
CALL TOLL-FREE IN THE U.S. AND
CANADA 800-544-2444